



Rated current SEC: **1,5 - 14A**
 Rated voltage PRI: **230V 50/60Hz**
 Control type: **5-step regulation**

Autotransformer fan speed controllers serve the purpose of airflow control in single-phase fan motors controlled by voltage. Open version, designed for installation in industrial ventilation or heating systems. A five-stage output voltage available from the subsequent taps of the autotransformer, led out to the electrical connector. Made with Class I insulation and protection grade IP00. Maximum ambient temperature 40°C, thermal class of insulation B (130°C). Manufactured in compliance with EN61558-2-13.

Type	Current	Dimensions [mm]					Mounting	Weight [kg]
	[A]	A	B	C	D	E		
ARM 1,5	1,5	84	60	100	64	46	M4	1,60
ARM 2,0	2,0	84	60	100	64	46	M4	1,60
ARM 3,0	3,0	84	74	100	64	60	M4	1,90
ARM 5,0	5,0	96	86	115	84	70	M5	2,60
ARM 7,0	7,0	120	88	130	90	70	M5	3,80
ARM 10,0	10,0	120	100	130	90	82	M5	4,70
ARM 14,0	14,0	150	117	175	122	87	M6	7,80

Type	Current	Example models Ur [V]				
	[A]	1	2	3	4	5
ARM 1,5/2	1,5	230	180	155	135	115
ARM 2,0/2	2,0	230	170	135	105	80
ARM 2,0/3	2,0	230	180	155	135	115
ARM 3,0/1	3,0	230	180	155	135	115
ARM 3,0/4	3,0	230	170	135	105	80
ARM 5,0/1	5,0	230	160	130	105	80
ARM 5,0/2	5,0	230	180	155	135	115
ARM 7,0/1	7,0	230	160	130	105	80
ARM 7,0/2	7,0	230	170	135	105	80
ARM 7,0/3	7,0	230	180	155	135	115
ARM 10,0/1	10,0	230	170	135	105	80
ARM 14,0/1	14,0	230	170	135	105	80

Due to the constant development of the construction and changes in technical requirements, Breve Tufassons reserves the right to change the above parameters.