



ARWD 1,5 - 10,0

ARWD 14,0

Rated current SEC: **1,5 - 14A**  
 Rated voltage PRI: **230V 50/60Hz**  
 Control type: **5-step regulation**

Autotransformer, single-phase, two-speed fan speed controllers equipped with a fuse. Switching between settings is done by shorting or opening CL-CL contacts, e.g. by an external clock. Regulators are equipped with two knobs, thanks to which the fan speed can be programmed, e.g. during the day and at night, and with two lights - green indicating power supply and red indicating motor thermal contact activation. Connecting thermocontacts protects the fan motor against overheating (the controller is switched off). ARWD/S/R version has a reset button for starting the regulator after the thermocontact has operated - controller does not switch on automatically. Made with Class II insulation and protection grade IP21 (ARWD 10 - 14) or IP54 (ARWD 1,5 - 7), max ambient temperature 40°C. Thermal class of insulation B (130°C). Manufactured in compliance with EN61558-2-13.

Type	Current	Dimensions [mm]					Mounting	Weight [kg]
	[A]	A	B	C	D	E		
ARWD 1,5/S	1,5	123	240	125	105	220	M6	3,5
ARWD 1,5/S/R/2	1,5	123	240	125	105	220	M6	3,5
ARWD 3,0/S	3,0	123	240	125	105	220	M6	5,0
ARWD 3,0/S/R/2	3,0	123	240	125	105	220	M6	5,0
ARWD 5,0/S	5,0	147	277	155	113	255	M6	7,0
ARWD 5,0/S/R/2	5,0	147	277	155	113	255	M6	7,0
ARWD 7,0/S	7,0	147	277	155	113	255	M6	8,0
ARWD 7,0/S/R/2	7,0	147	277	155	113	255	M6	8,0
ARWD 10,0/S	10,0	147	277	155	113	255	M6	9,5
ARWD 14,0/S	14,0	340	195	300	320	175	M6	12,0

Type	Upri [V]	Voltage level	Steps of regulation Ur [V]				
			1	2	3	4	5
ARWD 1,5 - 14,0	230	HIGH	120	150	170	190	230
		LOW	80	100	120	150	170