



Rated current SEC: **1,5 - 14A**  
 Rated voltage PRI: **3 x 400V 50/60Hz**  
 Control type: **5-step regulation**

Three-phase autotransformer fan speed controllers applicable to voltage-controllable motors to control the rotational speed of fans and ventilation systems. Regulators are equipped with two indicators - the green one shows when the regulator is on while the red one shows when the TK contact is on. These controllers make it possible to select two optimal motor speeds and to switch these with a contact. Important energy savings and an increase of comfort can be achieved, for example by day and night control. Regulators are fitted with TK contacts for thermal motor protection and run/stop contacts for remote control. Made with Class II insulation and protection grade IP21, max ambient temperature 25°C, thermal class of insulation B (130°C). Manufactured in compliance with EN61558-2-13.

Type	Current	Dimensions [mm]					Mounting	Weight [kg]
	[A]	A	B	C	D	E		
<b>A3RWD 1,5/S</b>	1,5	268	160	280	250	190	M6	11
<b>A3RWD 2,0/S</b>	2,0	268	160	280	250	190	M6	12,7
<b>A3RWD 4,0/S</b>	4,0	340	195	300	320	175	M6	16
<b>A3RWD 7,0/S</b>	7,0	340	195	300	320	175	M6	22
<b>A3RWD 10,0/S</b>	10,0	400	230	355	380	207	M6	32
<b>A3RWD 14,0/S</b>	14,0	400	230	355	380	207	M6	39

Type	Upri	Voltage level	Steps of regulation				
	[V]		Ur [V]/Ir [A]				
			1	2	3	4	5
<b>A3RWD 1,5 - 14,0</b>	3x400	HIGH LOW	3x210 3x130	3x250 3x170	3x290 3x210	3x330 3x250	3x400 3x290