



Power: **20; 30W**  
 Rated voltage PRI: **90 - 264V AC 47/63Hz ; 145 - 270V DC**  
 Rated voltage SEC: **12; 24V +5%**  
 Efficiency: **82 - 86% (typical)**

Pulse power supplies specially designed for residential and office applications. Their modular housing and TH-35 bus holder allow installation in typical switchgears. Aesthetic housing with a springy handle allows for easy installation. Made in insulation class II. Housing made of self-extinguishing plastic. The availability of 12VDC and 24VDC voltages allows the use of power supplies to power various industrial automation devices. The power supplies have short-circuit, overload and overvoltage protections. Protection grade IP20, max ambient temperature 40°C. Made in compliance with the safety standard EN61558-2-16 and the magnetic compatibility standard EN61000-4-22,3,4,5,6,8,11.

Type	Power	Usek	Current	Dimensions [mm]					Weight [kg]
	[W]	[V]	[A]	A	B	C	D	E	
<b>PSLR 20N/12VDC</b>	20	12	1,6	54	94	50	92	46	0,3
<b>PSLR 20N/24VDC</b>	20	24	0,8	54	94	50	92	46	0,3
<b>PSLR 30N/12VDC</b>	30	12	2,5	54	94	50	92	46	0,4
<b>PSLR 30N/24VDC</b>	30	24	1,25	54	94	50	92	46	0,4