



Rated power: **30 - 2500VA**  
 Rated voltage PRI: **230; 400V 50/60Hz**  
 Rated voltage SEC: **24 - 230V**

Modern and economical opened build of general purpose transformers with single chamber for installation in industrial and electromagnetic installations and devices. The transformers are made with Class I insulation and protection grade IP00. Maximum ambient temperature 40°C, thermal class of insulation B (130°C). Manufactured in compliance with EN61558-2-4 and EN61558-2-6.

Type	Power	Dimensions [mm]					Mounting	Weight [kg]
	[VA]	A	B	C	D	E		
STM 30	30	66	53	59	50	40	M4	0,80
STM 50	50	66	78	77	50	52	M4	0,90
STM 63	63	78	60	80	56	48	M4	1,10
STM 80	80	84	61	95	64	47	M4	1,30
STM 100	100	84	75	95	64	61	M4	1,80
STM 130	130	96	77	114	84	60	M5	2,10
STM 160	160	96	87	114	84	70	M5	2,60
STM 200	200	96	87	114	84	70	M5	2,80
STM 250	250	96	100	114	84	92	M5	3,20
STM 320	320	120	88	125	90	70	M5	3,70
STM 400	400	120	103	125	90	82	M5	4,60
STM 500	500	120	120	125	90	102	M5	6,20
STM 630	630	150	120	155	122	89	M5	8,30
STM 800	800	150	135	155	122	106	M6	10,40
STM 1000	1000	150	160	155	122	130	M5	13,00
STM 1300	1300	174	152	175	125	128	M8	15,60
STM 1600	1600	174	162	175	125	138	M6	18,00
STM 2000	2000	192	152	185	150	122	M8	23,40
STM 2500	2500	192	174	185	150	144	M8	26,00