



Rated power: **1,5 - 10kVA**  
 Rated voltage PRI: **110 - 1000V 50/60Hz**  
 Rated voltage SEC: **24 - 500V**  
 Short circuit voltage: **<4%**

Opened build of general purpose transformers for building into installations and industrial or power engineering devices. The transformers are made with Class I insulation and protection grade IP00, maximum ambient temperature 40°C, thermal class of insulation B (130°C). Transformer core made with low-dissipative material, impregnation reinforced with thermosetting resin. Manufactured in compliance with EN61558.

Type	Power	Dimensions [mm]					Mounting	Weight [kg]
	[kVA]	A	B	C	D	E		
<b>T3M 1501</b>	1,50	230	90	225	176	71	9x13	14,00
<b>T3M 2001</b>	2,00	230	114	225	176	95	9x13	19,30
<b>T3M 2501</b>	2,50	265	120	255	200	90	10x18	24,80
<b>T3M 3201</b>	3,20	265	132	260	200	102	10x18	29,60
<b>T3M 4001</b>	4,00	300	135	290	224	107	10x18	35,00
<b>T3M 5001</b>	5,00	300	147	290	224	119	10x18	42,00
<b>T3M 6301</b>	6,30	360	153	380	264	127	10x18	53,00
<b>T3M 8001</b>	8,00	360	168	380	264	142	10x18	64,00
<b>T3M 10001</b>	10,00	420	173	430	316	143	13x20	85,00