



Rated power: **10 - 200VA**
 Rated voltage PRI: **24 - 500V 50/60Hz**
 Rated voltage SEC: **6 - 400V**

Cast resin transformers predominantly intended for assemblies of power supplies of electronic equipment with several connection options. They are characterized by small dimensions and compact construction as well as increased resistance to mechanical and climatic factors. The transformers are made with Class II insulation and protection grade from IP00 to IP20, maximum ambient temperature 40°C, thermal class of insulation B (130°C). Manufactured in compliance with EN61558-2-4, EN61558-2-6 and EN61558-2-1.

Type	Power [VA]	Dimensions [mm]						d x d1	Weight [kg]
		A	B	B1	C	D	E		
TZB 10	10	38,6	51,0	75,0	43,0	12,0	62,0	3,5x6,7	0,35
TZB 16	16	42,8	57,5	82,5	48,5	11,0	68,0	3,5x6,7	0,45
TZB 20	20	48,0	63,5	88,0	53,5	13,5	75,0	5x9	0,60
TZB 35	35	49,2	69,5	94,0	58,5	13,0	82,0	4,8x8,3	0,80
TZB 50	50	61,0	69,5	94,0	58,5	37,5	82,0	4,8x8,3	1,00
TZB 63	63	59,0	86,3	112,5	71,5	32,5	97,5	5,2x10	1,40
TZB 80	80	63,8	93,5	120,0	74,7	32,5	102,5	5,5x10	1,70
TZB 100	100	77,8	93,5	120,0	74,7	45,0	102,5	5,5x10	2,10
TZB 140	140	77,8	93,5	120,0	74,7	45,0	102,5	5,5x10	2,80
TZB 160	160	74,6	106,7	133,0	85,0	40,0	115,0	5,5x10	2,60
TZB 200	200	84,6	106,7	133,0	85,0	50,0	115,0	5,5x10	3,00