



Rated power: **1,6 - 12kVA**
 Rated voltage PRI: **110 - 1000V 50/60Hz**
 Rated voltage SEC: **12 - 500V**

Single-phase encased transformers of general purpose for building into installations and industrial or power engineering devices. The transformers are made with Class I insulation and protection rating of IP23, maximum ambient temperature 40°C, thermal class of insulation: B (130°C). Manufactured in compliance with EN61558.

Variations coding: **PUM (x)(y)**, e.g. PUM 2501 where:
(x) - number equals to 1/10 of power rating in VA;
(y) - type of winding: „**0**” - dual chamber, low dissipation;
 „**1**” - single chamber frame, low dissipation; „**2**” - single chamber, standard core.

| Type | Power [kVA] | Dimensions [mm] | | | | | | Mounting | Weight [kg] |
|------------------|----------------|-----------------|-----|-----|-----|-----|-----|----------|----------------|
| | | A | B | C | D | E | F | | |
| PUM 160y | 1,6 | 270 | 320 | 415 | 290 | 124 | 250 | M10 | 22,9 |
| PUM 200y | 2,0 | 270 | 320 | 415 | 290 | 124 | 250 | M10 | 25,4 |
| PUM 250y | 2,5 | 270 | 320 | 415 | 290 | 124 | 250 | M10 | 27,6 |
| PUM 320y | 3,2 | 270 | 320 | 415 | 290 | 124 | 250 | M10 | 30,6 |
| PUM 400y | 4,0 | 270 | 320 | 415 | 290 | 124 | 250 | M10 | 33,6 |
| PUM 500y | 5,0 | 410 | 450 | 580 | 390 | 144 | 360 | M12 | 48,6 |
| PUM 630y | 6,3 | 410 | 450 | 580 | 390 | 144 | 360 | M12 | 54,6 |
| PUM 800y | 8,0 | 410 | 450 | 580 | 390 | 144 | 360 | M12 | 67,6 |
| PUM 1000y | 10,0 | 410 | 450 | 580 | 390 | 144 | 360 | M12 | 72,6 |
| PUM 1200y | 12,0 | 410 | 450 | 580 | 390 | 144 | 360 | M12 | 79,6 |